



QWIK-FENCE® PARTITIONS



MADE IN THE USA

GALVANIZED WIRE WELDED IN A GRID PATTERN CREATES AN ATTRACTIVE AND SECURE SYSTEM FOR SEPARATING SPACES

▶ UNSURPASSED ADJUSTABILITY

The Qwik-Fence® System can be easily adapted on-site to meet your specific needs.

▶ IN STOCK

We keep a large stock of our standard components in-house to ensure quick shipping for your urgent security needs.

▶ PRE-ENGINEERED ROOMS

Available in multiple configurations, the Qwik-Fence® system ships pre-packaged, making it quick to set up and easy to relocate.

Qwik-Fence® Welded Wire Partitions are an extremely tough and attractive system for separating and securing any space. Welded at each intersection—over 500 welds in a 4' x 8' panel—this wire mesh partition is substantially stronger than woven wire alternatives.

True to their name, Qwik-Fence® Partitions install 25% faster than substitutes by employing fewer parts and utilizing self-tapping screws. The partitions are easily reconfigurable, flexible and the galvanized finish will keep the system looking new for years to come.



Multiple locking options are available (cylinder lock shown)



All slide doors come with sturdy tracks



QWIK-FENCE® PARTITIONS



PANELS

PART No.	W x H	WEIGHT
10x5	10' x 5'	46 lbs.
10x4	10' x 4'	37 lbs.
10x3	10' x 3'	28 lbs.
10x2	10' x 2'	19 lbs.
10x1	10' x 1'	10 lbs.
8x5	8' x 5'	37 lbs.
8x4	8' x 4'	29 lbs.
8x3	8' x 3'	23 lbs.
8x2	8' x 2'	16 lbs.
8x1	8' x 1'	9 lbs.

POSTS

PART No.	HEIGHT	DESCRIPTION	WEIGHT
P8	8'	Universal	20 lbs.
P8 Flat	8'	Flat	25 lbs.
P8 Flat/Offset	8'	Flat/Offset	25 lbs.
XP1	1'	Extension	4 lbs.
XP2	2'	Extension	6 lbs.
XP3	3'	Extension	8 lbs.
XP4	4'	Extension	10 lbs.
XP6	6'	Extension	17 lbs.
XP8	8'	Extension	19 lbs.

OPTIONS

PART No.	DESCRIPTION	WEIGHT
CA8	Ceiling Wall Angle	5 lbs.
WK	Wall Kit	8 lbs.
SWK	Service Window Kit	55 lbs.
PXT	Post Top Extension	5 lbs.
WIR CUTR	Wire Cutter	5 lbs.
TK-10	Transom Kit to fit 8' Door into 10' frame	3 lbs.
TK-12	Transom Kit to fit 10' Door into 12' frame	6 lbs.
Consult Factory	Capping Channel 96"	0.9 lb/ft
RST	Roof Support Tube	2 lb/ft
Consult Factory	Roof	-

DOORS

WIDTH	8' High		10' High		12' High	
	PART No.	WEIGHT	PART No.	WEIGHT	PART No.	WEIGHT
Hinge Door						
3'	QF-H38	64 lbs.	Consult factory	-	-	-
4'	QF-H48	75 lbs.	Consult factory	-	-	-
Hinge Pair Door						
6'	QF-HP68	160 lbs.	Consult factory	-	-	-
8'	QF-HP88	190 lbs.	Consult factory	-	-	-
Slide Door*						
3'	QF-S38	88 lbs.	Consult factory	Consult factory	Consult factory	Consult factory
4'	QF-S48	100 lbs.	S-410	129 lbs.	S-412	155 lbs.
5'	QF-S58	132 lbs.	S-510	160 lbs.	S-512	192 lbs.
6'	QF-S68	143 lbs.	S-610	178 lbs.	S-612	211 lbs.
8'	QF-S88	170 lbs.	S-810	273 lbs.	S-812	328 lbs.
10'	QF-S108	249 lbs.	S-1010	308 lbs.	S-1012	367 lbs.
Slide Pair Door*						
8'	QF-SP88	236 lbs.	SP8-10	279 lbs.	SP8-12	335 lbs.
10'	QF-SP108	265 lbs.	SP10-10	312 lbs.	SP10-12	374 lbs.

*Note: Actual sliding door exceeds opening width. Please consult factory for exact dimension.

LOCKING OPTIONS

	Door Type			
	H	HP	S	SP
Padlock Hasp	✓	✓	✓	✓
Cylinder Lock (Key Lock Not Included)	✓	✓	✓	✓
Keyed Alike Cylinders	✓	✓	✓	✓
Keyed Different Cylinders	✓	✓	✓	✓
Cylinder to Accept Interchangeable Core	✓	✓	✓	✓
Thumbturn	✓	✓	✓	✓
Hydraulic Closer	✓	✓		
Pushbar Exit Device	✓	✓		
Deadlatch Paddle	✓	✓		
Lever Handle	✓	✓		
Electric Strike	✓	✓		
Magnetic Lock	✓	✓	✓	✓
Keypad Lock	✓	✓	✓	✓
Proximity Reader	✓	✓	✓	✓
Magstripe Card Reader	✓	✓	✓	✓
Exit Button	✓	✓	✓	✓

SPECIFICATIONS

Panels	
Wire	8-gauge welded
Grid Opening	1 1/2" x 3"
Finish	Galvanized
Posts	
Tube	2" x 2", 14-gauge
Foot Plate	6" x 2" x 1/4"
Doors	
Wire	10-gauge welded
Grid Opening	1 1/4" x 2 1/2"
Finish	Powder Coated
General	
Warranty	1 Year



Hinge Door



Slide Door



Hinge Pair Door